

Amendments to the Claims:

1. (Currently Amended) ~~A system for bi-directional communication~~ An apparatus comprising:

~~a first host capable of transmitting a processor configured to transmit multiplexed data at a first transmission rate and operating~~ operate with a first congestion window, wherein the ~~first host processor~~ is also capable of receiving configured to receive multiplexed data at a second transmission rate from a second host ~~capable of operating separate from the apparatus and configured to operate~~ with a second congestion window, and wherein the ~~first host processor~~ is capable of configuring configured to set at least one of a size of the first congestion window and a size of the second congestion window based upon the first transmission rate, the size of the second congestion window, the second transmission rate and the size of the first congestion window.

2. (Currently Amended) ~~A system~~ An apparatus according to Claim 1, wherein the ~~first host processor is capable of configuring configured to set~~ at least one of a size of the first congestion window and a size of the second congestion window such that a product of the first transmission rate and the size of the second congestion window approximately equals a product of the second transmission rate and the size of the first congestion window.

3. (Currently Amended) ~~A system~~ An apparatus according to Claim 1, wherein the second host is ~~capable of receiving configured to receive~~ multiplexed data into a second reception window from the ~~first host processor~~, wherein the ~~first host processor~~ is capable of configuring configured to set a size of the first congestion window based upon a maximum size of the first congestion window, and wherein the ~~first host processor~~ is capable of configuring configured to set the maximum size of the first congestion window based upon a size of the second reception window.

4. (Currently Amended) ~~A system~~ An apparatus according to Claim 1, wherein the

~~first host processor is capable of receiving~~ configured to receive multiplexed data into a first reception window, and wherein the ~~first host processor is capable of configuring~~ configured to set the size of the second congestion window based upon a size of the first reception window.

5. (Currently Amended) ~~A system~~ An apparatus according to Claim 4, wherein the ~~first host is capable of configuring~~ processor being configured to set the size of the second congestion window ~~by~~ includes being configured to:

~~determining~~ determine a size of the first reception window based upon a maximum size of the first congestion window and the first and second transmission rates; and

~~transmitting~~ transmit multiplexed data to the second host indicating the size of the first reception window such that the second host configures the size of the second congestion window based upon the size of the first reception window.

6. (Currently Amended) ~~A system~~ An apparatus according to Claim 5, wherein the ~~first host is capable of determining~~ processor being configured to determine a size of the first reception window ~~by multiplying~~ includes being configured to multiply the maximum size of the first congestion window by the second transmission rate and dividing the product by the first transmission rate.

7. (Currently Amended) ~~A system~~ An apparatus according to Claim 1, wherein the ~~first host processor is capable of~~ configured to continuously ~~transmitting~~ transmit multiplexed data and ~~receiving~~ receive multiplexed data from the second host, and wherein the ~~first host processor is capable of~~ configured to continuously ~~configuring~~ set at least one of the size of the ~~first congestion window and the size of the second congestion window~~.

8. (Currently Amended) A method of bi-directional communication between a first host and a separate, second host, the method comprising:

transmitting multiplexed data at a first transmission rate from the first host operating with a first congestion window;

receiving multiplexed data at a second transmission rate from the second host operating with a second congestion window; and

configuring at the first host at least ~~one of a size of the first congestion window and a size~~ of the second congestion window based upon the first transmission rate, the size of the second congestion window, the second transmission rate and the size of the first congestion window.

9. (Currently Amended) A method according to Claim 8, wherein configuring at least ~~one of the size of the first congestion window and the size of the second congestion window~~ comprises configuring at least ~~one of the size of the first congestion window and the size of the~~ second congestion window such that a product of the first transmission rate and the size of the second congestion window approximately equals a product of the second transmission rate and the size of the first congestion window.

10. (Original) A method according to Claim 8, wherein the second host is capable of receiving multiplexed data into a second reception window from the first host, wherein configuring a size of the first congestion window comprises configuring a size of the first congestion window based upon a maximum size of the first congestion window, and wherein configuring a maximum size of the first congestion window comprises configuring a maximum size of the first congestion window based upon a size of the second reception window.

11. (Original) A method according to Claim 8, wherein receiving multiplexed data comprises receiving multiplexed data into a first reception window, and wherein configuring a size of the second congestion window comprises configuring a size of the second congestion window based upon a size of the first reception window.

12. (Original) A method according to Claim 11, wherein configuring a size of the second congestion window comprises:

determining a size of the first reception window based upon a maximum size of the first congestion window and the first and second transmission rates; and

transmitting multiplexed data to the second host indicating the size of the first reception window such that the second host configures the size of the second congestion window based upon the size of the first reception window.

13. (Original) A method according to Claim 12, wherein determining a size of the first reception window comprises determining a size of the first reception window by multiplying the maximum size of the first congestion window by the second transmission rate and dividing the product by the first transmission rate.

14. (Currently Amended) A method according to Claim 8, wherein transmitting multiplexed data and receiving multiplexed data comprise continuously transmitting multiplexed data and receiving multiplexed data, respectively, and wherein configuring at least ~~one of a size of the first congestion window and a size of the second congestion window~~ comprises continuously configuring at least ~~one of a size of the first congestion window and a size of the second congestion window~~.

15. (Currently Amended) A ~~computer program product for bi-directional communication between a first host and a second host, the computer program product comprising a computer-readable storage medium having computer-readable program code portions stored therein, the computer-readable program code portions comprising:~~

a first executable portion for transmitting multiplexed data at a first transmission rate from ~~the a~~ first host operating with a first congestion window, the first host being configured to bi-directionally communicate with a separate, second host;

a second executable portion for receiving multiplexed data at a second transmission rate from the second host operating with a second congestion window; and

a third executable portion for configuring at the first host at least ~~one of a size of the first congestion window and a size of the second congestion window~~ based upon the first transmission rate, the size of the second congestion window, the second transmission rate and the size of the first congestion window.

16. (Currently Amended) A ~~computer program product~~ computer-readable storage medium according to Claim 15, wherein the third executable portion is adapted to configure at least one of the size of the first congestion window and the size of the second congestion window such that a product of the first transmission rate and the size of the second congestion window approximately equals a product of the second transmission rate and the size of the first congestion window.

17. (Currently Amended) A ~~computer program product~~ computer-readable storage medium according to Claim 15, wherein the second host is capable of receiving multiplexed data into a second reception window from the first host, wherein the third executable portion is adapted to configure the size of the first congestion window based upon a maximum size of the first congestion window, and wherein the third executable portion is adapted to configure the maximum size of the first congestion window co based upon a size of the second reception window.

18. (Currently Amended) A ~~computer program product~~ computer-readable storage medium according to Claim 15, wherein the first executable portion is adapted to receive multiplexed data into a first reception window, and wherein the third executable portion is adapted to configure the size of the second congestion window based upon a size of the first reception window.

19. (Currently Amended) A ~~computer program product~~ computer-readable storage medium according to Claim 18, wherein the third executable portion is being adapted to configure the size of the second congestion window by includes being adapted to:

~~determining~~ determine a size of the first reception window based upon a maximum size of the first congestion window and the first and second transmission rates; and

~~transmitting~~ transmit multiplexed data to the second host indicating the size of the first reception window such that the second host configures the size of the second congestion window

based upon the size of the first reception window.

20. (Currently Amended) A ~~computer program product~~ computer-readable storage medium according to Claim 19, wherein the third executable portion is adapted to determine a size of the first reception window by multiplying the maximum size of the first congestion window by the second transmission rate and dividing the product by the first transmission rate.

21. (Currently Amended) A ~~computer program product~~ computer-readable storage medium according to Claim 15, wherein the first and second executable portions are adapted to continuously transmit multiplexed data and receive multiplexed data, respectively, and wherein the third executable portion is adapted to continuously configure at least ~~one of a size of the first congestion window and a size of the second congestion window.~~